

Precalculated Metal Chime Dimensions

- For 0.065 inch wall thickness Brass family
- Tubing sized in inches
- Length and hang-point listed for inches & mm
- Select chime size from the menu to the left of this page

Caution: if you are attempting to create exact notes for an orchestra setting, exact tuning is required and the use of an electronic tuning device or a good tuning ear is necessary. On the other hand, if you desire a good sounding set of chimes but do not need orchestra accuracy, then carefully cut the tube to the length suggested by this pre-calculated table, or the DIY calculator listed on the website.

Do not use these calculations for an orchestra or a musical setting unless you know for sure they tune to A4=440 Hz. An orchestra will typically tune for A4= 442, 43 or 44 Hz and this chart uses A4=440 Hz. Most symphony grade instruments are shipped with A4=442 Hz.

Caution: While there are a host of apps for Chromatic Tuners available for an iPhone, iPad or Android, measuring the exact frequency and musical note of the chime is challenging at best. Non linearity of the human ear and the chime's non-harmonic overtones are two reasons.

It is difficult to provide an exact recommendation when to use the a chromatic tuner to measure a chime's note, but in general, I find most any note below C4 difficult to measure and on occasion below C5. Long, low frequencies tubes, measure incorrectly because of the "missing fundamental effect", and the preponderance of high amplitude overtones. Thick-walled tank chimes/bells can measure with surprising accuracy because its single pure tone above C4 is not cluttered with unimportant sidebands. More info about this topic is here: www.leehite.org/Chimes.htm#Tuning:

From:

www.leehite.org/Chimes.htm

Tubular Wind Chime Dimensions

Brass .065 Wall Nominal size = 1/2"

A=440 Hz, tube open at both ends

OD inches = 0.500	ID inches = 0.370	Material = Brass
--------------------------	--------------------------	-------------------------

Wall = 0.065 inches * Tubing length calculated for fundamental frequency ** Hang Point is for fundamental frequency node

Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm	Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm
C1	32.70	49 3/4	11 1/8	1,262.7	283.1	C5	523.30	12 7/16	2 13/16	315.7	70.8
C#/D ^b	34.60	48 3/8	10 7/8	1,227.8	275.3	C#/D ^b	554.40	12 1/16	2 11/16	306.1	68.6
D	36.70	47	10 9/16	1,192.9	267.4	D	587.30	11 3/4	2 5/8	298.2	66.9
D#/E ^b	38.90	45 5/8	10 1/4	1,158.0	259.6	D#/E ^b	622.30	11 7/16	2 9/16	290.3	65.1
E	41.21	44 5/16	9 15/16	1,124.7	252.1	E	659.30	11 1/16	2 1/2	280.8	62.9
F	43.70	43 1/16	9 5/8	1,092.9	245.0	F	698.50	10 3/4	2 7/16	272.8	61.2
F#/G ^d	46.30	41 13/16	9 3/8	1,061.2	237.9	F#/G ^d	740.00	10 7/16	2 5/16	264.9	59.4
G	49.00	40 11/16	9 1/8	1,032.6	231.5	G	784.00	10 3/16	2 5/16	258.6	58.0
G#/A ^d	51.90	39 1/2	8 7/8	1,002.5	224.8	G#/A ^d	830.60	9 7/8	2 3/16	250.6	56.2
A	55.01	38 3/8	8 5/8	974.0	218.4	A	880.00	9 5/8	2 3/16	244.3	54.8
A#/B ^d	58.30	37 5/16	8 3/8	947.0	212.3	A#/B ^d	932.30	9 5/16	2 1/16	236.4	53.0
B	61.70	36 1/4	8 1/8	920.0	206.3	B	987.80	9 1/16	2 1/16	230.0	51.6
C2	65.40	35 3/16	7 7/8	893.1	200.2	C6	1,046.50	8 13/16	2	223.7	50.1
C#/D ^b	69.30	34 3/16	7 11/16	867.7	194.5	C#/D ^b	1,108.70	8 9/16	1 15/16	217.3	48.7
D	73.41	33 1/4	7 7/16	843.9	189.2	D	1,174.61	8 5/16	1 7/8	211.0	47.3
D#/E ^b	77.80	32 1/4	7 1/4	818.5	183.5	D#/E ^b	1,244.50	8 1/16	1 13/16	204.6	45.9
E	82.40	31 3/8	7 1/16	796.3	178.5	E	1,318.50	7 13/16	1 3/4	198.3	44.5
F	87.30	30 7/16	6 13/16	772.5	173.2	F	1,397.00	7 5/8	1 11/16	193.5	43.4
F#/G ^d	92.50	29 5/8	6 5/8	751.9	168.6	F#/G ^d	1,480.00	7 3/8	1 5/8	187.2	42.0
G	98.01	28 3/4	6 7/16	729.7	163.6	G	1,568.00	7 3/16	1 5/8	182.4	40.9
G#/A ^d	103.80	27 15/16	6 1/4	709.1	159.0	G#/A ^d	1,661.20	7	1 9/16	177.7	39.8
A	110.00	27 1/8	6 1/16	688.4	154.3	A	1,760.00	6 13/16	1 1/2	172.9	38.8
A#/B ^d	116.50	26 3/8	5 15/16	669.4	150.1	A#/B ^d	1,864.60	6 9/16	1 1/2	166.6	37.3
B	123.50	25 5/8	5 3/4	650.4	145.8	B	1,975.50	6 3/8	1 7/16	161.8	36.3
C3	130.81	24 7/8	5 9/16	631.3	141.5	C7	2,093.00	6 1/4	1 3/8	158.6	35.6
C#/D ^b	138.60	24 3/16	5 7/16	613.9	137.6	C#/D ^b	2,217.40	6 1/16	1 3/8	153.9	34.5
D	146.80	23 1/2	5 1/4	596.4	133.7	D	2,349.20	5 7/8	1 5/16	149.1	33.4
D#/E ^b	155.60	22 13/16	5 1/8	579.0	129.8	D#/E ^b	2,489.01	5 11/16	1 1/4	144.3	32.4
E	164.80	22 3/16	5	563.1	126.3	E	2,637.00	5 9/16	1 1/4	141.2	31.7
F	174.61	21 9/16	4 13/16	547.3	122.7	F	2,794.00	5 3/8	1 3/16	136.4	30.6
F#/G ^d	185.00	20 15/16	4 11/16	531.4	119.1	F#/G ^d	2,960.00	5 1/4	1 3/16	133.2	29.9
G	196.00	20 5/16	4 9/16	515.5	115.6	G	3,136.00	5 1/16	1 1/8	128.5	28.8
G#/A ^d	207.70	19 3/4	4 7/16	501.3	112.4	G#/A ^d	3,322.41	4 15/16	1 1/8	125.3	28.1
A	220.00	19 3/16	4 5/16	487.0	109.2	A	3,520.00	4 13/16	1 1/16	122.1	27.4
A#/B ^d	233.10	18 5/8	4 3/16	472.7	106.0	A#/B ^d	3,729.20	4 11/16	1 1/16	119.0	26.7
B	246.90	18 1/8	4 1/16	460.0	103.1	B	3,951.00	4 1/2	1	114.2	25.6
C4	261.60	17 5/8	3 15/16	447.3	100.3	C8	4,186.00	4 3/8	1	111.0	24.9
C#/D ^b	277.20	17 1/8	3 13/16	434.6	97.4	C#/D ^b	4,434.81	4 1/4	15/16	107.9	24.2
D	293.70	16 5/8	3 3/4	421.9	94.6	D	4,698.40	4 1/8	15/16	104.7	23.5
D#/E ^b	311.10	16 1/8	3 5/8	409.3	91.8	D#/E ^b	4,978.00	4 1/16	15/16	103.1	23.1
E	329.61	15 11/16	3 1/2	398.1	89.3	E	5,274.00	3 15/16	7/8	99.9	22.4
F	349.30	15 1/4	3 7/16	387.0	86.8	F	5,588.00	3 13/16	7/8	96.8	21.7
F#/G ^d	370.00	14 13/16	3 5/16	375.9	84.3	F#/G ^d	5,920.00	3 11/16	13/16	93.6	21.0
G	392.00	14 3/8	3 1/4	364.8	81.8	G	6,272.00	3 5/8	13/16	92.0	20.6
G#/A ^d	415.30	13 15/16	3 1/8	353.7	79.3	G#/A ^d	6,644.80	3 1/2	13/16	88.8	19.9
A	440.01	13 9/16	3 1/16	344.2	77.2	A	7,040.00	3 3/8	3/4	85.7	19.2
A#/B ^d	466.20	13 3/16	2 15/16	334.7	75.0	A#/B ^d	7,458.40	3 5/16	3/4	84.1	18.8
B	493.91	12 13/16	2 7/8	325.2	72.9	B	7,902.01	3 3/16	11/16	80.9	18.1
						C9	8,367.01	3 1/8	11/16	79.3	17.8

www.home.fuse.net/engineering/Chimes.htm

Caution, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, but not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A=442, 43 or 44.

Tubular Wind Chime Dimensions

Brass .065 Wall Nominal size = 3/4"

A=440 Hz, tube open at both ends

OD inches = 0.750	ID inches = 0.620	Material = Brass
--------------------------	--------------------------	-------------------------

Wall = 0.065 inches * Tubing length calculated for fundamental frequency ** Hang Point is for fundamental frequency node

Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm	Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm
C1	32.70	62 1/4	13 15/16	1,579.9	354.2	C5	523.30	15 9/16	3 1/2	395.0	88.6
C [#] /D ^b	34.60	60 1/2	13 9/16	1,535.5	344.3	C [#] /D ^b	554.40	15 1/8	3 3/8	383.9	86.1
D	36.70	58 3/4	13 3/16	1,491.1	334.3	D	587.30	14 11/16	3 5/16	372.8	83.6
D [#] /E ^b	38.90	57 1/16	12 13/16	1,448.2	324.7	D [#] /E ^b	622.30	14 1/4	3 3/16	361.7	81.1
E	41.21	55 7/16	12 7/16	1,407.0	315.5	E	659.30	13 7/8	3 1/8	352.1	79.0
F	43.70	53 7/8	12 1/16	1,367.3	306.6	F	698.50	13 1/2	3	342.6	76.8
F [#] /G ^b	46.30	52 5/16	11 3/4	1,327.7	297.7	F [#] /G ^b	740.00	13 1/16	2 15/16	331.5	74.3
G	49.00	50 7/8	11 3/8	1,291.2	289.5	G	784.00	12 11/16	2 7/8	322.0	72.2
G [#] /A ^b	51.90	49 7/16	11 1/16	1,254.7	281.3	G [#] /A ^b	830.60	12 3/8	2 3/4	314.1	70.4
A	55.01	48	10 3/4	1,218.2	273.1	A	880.00	12	2 11/16	304.6	68.3
A [#] /B ^b	58.30	46 5/8	10 7/16	1,183.3	265.3	A [#] /B ^b	932.30	11 11/16	2 5/8	296.6	66.5
B	61.70	45 5/16	10 3/16	1,150.0	257.8	B	987.80	11 5/16	2 9/16	287.1	64.4
C2	65.40	44	9 7/8	1,116.7	250.4	C6	1,046.50	11	2 7/16	279.2	62.6
C [#] /D ^b	69.30	42 3/4	9 9/16	1,085.0	243.3	C [#] /D ^b	1,108.70	10 11/16	2 3/8	271.2	60.8
D	73.41	41 9/16	9 5/16	1,054.9	236.5	D	1,174.61	10 3/8	2 5/16	263.3	59.0
D [#] /E ^b	77.80	40 3/8	9 1/16	1,024.7	229.7	D [#] /E ^b	1,244.50	10 1/16	2 1/4	255.4	57.3
E	82.40	39 1/4	8 13/16	996.2	223.3	E	1,318.50	9 13/16	2 3/16	249.0	55.8
F	87.30	38 1/8	8 9/16	967.6	216.9	F	1,397.00	9 1/2	2 1/8	241.1	54.1
F [#] /G ^b	92.50	37	8 5/16	939.1	210.5	F [#] /G ^b	1,480.00	9 1/4	2 1/16	234.8	52.6
G	98.01	35 15/16	8 1/16	912.1	204.5	G	1,568.00	9	2	228.4	51.2
G [#] /A ^b	103.80	34 15/16	7 13/16	886.7	198.8	G [#] /A ^b	1,661.20	8 3/4	1 15/16	222.1	49.8
A	110.00	33 15/16	7 5/8	861.3	193.1	A	1,760.00	8 1/2	1 7/8	215.7	48.4
A [#] /B ^b	116.50	33	7 3/8	837.5	187.8	A [#] /B ^b	1,864.60	8 1/4	1 7/8	209.4	46.9
B	123.50	32 1/16	7 3/16	813.7	182.4	B	1,975.50	8	1 13/16	203.0	45.5
C3	130.81	31 1/8	7	790.0	177.1	C7	2,093.00	7 13/16	1 3/4	198.3	44.5
C [#] /D ^b	138.60	30 1/4	6 13/16	767.7	172.1	C [#] /D ^b	2,217.40	7 9/16	1 11/16	191.9	43.0
D	146.80	29 3/8	6 9/16	745.5	167.1	D	2,349.20	7 3/8	1 5/8	187.2	42.0
D [#] /E ^b	155.60	28 9/16	6 3/8	724.9	162.5	D [#] /E ^b	2,489.01	7 1/8	1 5/8	180.8	40.5
E	164.80	27 3/4	6 1/4	704.3	157.9	E	2,637.00	6 15/16	1 9/16	176.1	39.5
F	174.61	26 15/16	6 1/16	683.7	153.3	F	2,794.00	6 3/4	1 1/2	171.3	38.4
F [#] /G ^b	185.00	26 3/16	5 7/8	664.6	149.0	F [#] /G ^b	2,960.00	6 9/16	1 1/2	166.6	37.3
G	196.00	25 7/16	5 11/16	645.6	144.7	G	3,136.00	6 3/8	1 7/16	161.8	36.3
G [#] /A ^b	207.70	24 11/16	5 9/16	626.6	140.5	G [#] /A ^b	3,322.41	6 3/16	1 3/8	157.0	35.2
A	220.00	24	5 3/8	609.1	136.6	A	3,520.00	6	1 3/8	152.3	34.1
A [#] /B ^b	233.10	23 5/16	5 1/4	591.7	132.7	A [#] /B ^b	3,729.20	5 13/16	1 5/16	147.5	33.1
B	246.90	22 11/16	5 1/16	575.8	129.1	B	3,951.00	5 11/16	1 1/4	144.3	32.4
C4	261.60	22	4 15/16	558.4	125.2	C8	4,186.00	5 1/2	1 1/4	139.6	31.3
C [#] /D ^b	277.20	21 3/8	4 13/16	542.5	121.6	C [#] /D ^b	4,434.81	5 3/8	1 3/16	136.4	30.6
D	293.70	20 3/4	4 5/8	526.6	118.1	D	4,698.40	5 3/16	1 3/16	131.7	29.5
D [#] /E ^b	311.10	20 3/16	4 1/2	512.4	114.9	D [#] /E ^b	4,978.00	5 1/16	1 1/8	128.5	28.8
E	329.61	19 5/8	4 3/8	498.1	111.7	E	5,274.00	4 7/8	1 1/16	123.7	27.7
F	349.30	19 1/16	4 1/4	483.8	108.5	F	5,588.00	4 3/4	1 1/16	120.6	27.0
F [#] /G ^b	370.00	18 1/2	4 1/8	469.5	105.3	F [#] /G ^b	5,920.00	4 5/8	1 1/16	117.4	26.3
G	392.00	18	4 1/16	456.8	102.4	G	6,272.00	4 1/2	1	114.2	25.6
G [#] /A ^b	415.30	17 1/2	3 15/16	444.2	99.6	G [#] /A ^b	6,644.80	4 3/8	1	111.0	24.9
A	440.01	17	3 13/16	431.5	96.7	A	7,040.00	4 1/4	15/16	107.9	24.2
A [#] /B ^b	466.20	16 1/2	3 11/16	418.8	93.9	A [#] /B ^b	7,458.40	4 1/8	15/16	104.7	23.5
B	493.91	16	3 9/16	406.1	91.0	B	7,902.01	4	7/8	101.5	22.8
						C9	8,367.01	3 7/8	7/8	98.3	22.0

www.home.fuse.net/engineering/Chimes.htm

Caution, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, but not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A=442, 43 or 44.

Tubular Wind Chime Dimensions

Brass .065 Wall Nominal size = 1.0"

A=440 Hz, tube open at both ends

OD inches = 1.000	ID inches = 0.870	Material = Brass
--------------------------	--------------------------	-------------------------

Wall = 0.065 inches * Tubing length calculated for fundamental frequency ** Hang Point is for fundamental frequency node

Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm	Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm
C1	32.70	72 11/16	16 5/16	1,844.8	413.6	C5	523.30	18 3/16	4 1/16	461.6	103.5
C [#] /D ^b	34.60	70 5/8	15 13/16	1,792.5	401.9	C [#] /D ^b	554.40	17 5/8	3 15/16	447.3	100.3
D	36.70	68 5/8	15 3/8	1,741.7	390.5	D	587.30	17 1/8	3 13/16	434.6	97.4
D [#] /E ^b	38.90	66 5/8	14 15/16	1,690.9	379.1	D [#] /E ^b	622.30	16 11/16	3 3/4	423.5	95.0
E	41.21	64 3/4	14 1/2	1,643.4	368.4	E	659.30	16 3/16	3 5/8	410.8	92.1
F	43.70	62 7/8	14 1/8	1,595.8	357.8	F	698.50	15 3/4	3 1/2	399.7	89.6
F [#] /G ^b	46.30	61 1/16	13 11/16	1,549.8	347.5	F [#] /G ^b	740.00	15 1/4	3 7/16	387.0	86.8
G	49.00	59 3/8	13 5/16	1,506.9	337.9	G	780.00	14 13/16	3 5/16	375.9	84.3
G [#] /A ^b	51.90	57 11/16	12 15/16	1,464.1	328.3	G [#] /A ^b	830.60	14 7/16	3 1/4	366.4	82.2
A	55.01	56	12 9/16	1,421.3	318.7	A	880.00	14	3 1/8	355.3	79.7
A [#] /B ^b	58.30	54 7/16	12 3/16	1,381.6	309.8	A [#] /B ^b	932.30	13 5/8	3 1/16	345.8	77.5
B	61.70	52 7/8	11 7/8	1,342.0	300.9	B	987.80	13 1/4	3	336.3	75.4
C2	65.40	51 3/8	11 1/2	1,303.9	292.3	C6	1,046.50	12 7/8	2 7/8	326.8	73.3
C [#] /D ^b	69.30	49 15/16	11 3/16	1,267.4	284.2	C [#] /D ^b	1,108.70	12 1/2	2 13/16	317.3	71.1
D	73.41	48 1/2	10 7/8	1,230.9	276.0	D	1,174.61	12 1/8	2 11/16	307.7	69.0
D [#] /E ^b	77.80	47 1/8	10 9/16	1,196.0	268.2	D [#] /E ^b	1,244.50	11 3/4	2 5/8	298.2	66.9
E	82.40	45 3/4	10 1/4	1,161.1	260.3	E	1,318.50	11 7/16	2 9/16	290.3	65.1
F	87.30	44 1/2	10	1,129.4	253.2	F	1,397.00	11 1/8	2 1/2	282.4	63.3
F [#] /G ^b	92.50	43 3/16	9 11/16	1,096.1	245.7	F [#] /G ^b	1,480.00	10 13/16	2 7/16	274.4	61.5
G	98.01	42	9 7/16	1,066.0	239.0	G	1,568.00	10 1/2	2 3/8	266.5	59.7
G [#] /A ^b	103.80	40 13/16	9 1/8	1,035.8	232.2	G [#] /A ^b	1,661.20	10 3/16	2 5/16	258.6	58.0
A	110.00	39 5/8	8 7/8	1,005.7	225.5	A	1,760.00	9 7/8	2 3/16	250.6	56.2
A [#] /B ^b	116.50	38 1/2	8 5/8	977.1	219.1	A [#] /B ^b	1,864.60	9 5/8	2 3/16	244.3	54.8
B	123.50	37 3/8	8 3/8	948.6	212.7	B	1,975.50	9 3/8	2 1/8	237.9	53.3
C3	130.81	36 5/16	8 1/8	921.6	206.6	C7	2,093.00	9 1/16	2 1/16	230.0	51.6
C [#] /D ^b	138.60	35 5/16	7 15/16	896.2	200.9	C [#] /D ^b	2,217.40	8 13/16	2	223.7	50.1
D	146.80	34 5/16	7 11/16	870.9	195.2	D	2,349.20	8 9/16	1 15/16	217.3	48.7
D [#] /E ^b	155.60	33 5/16	7 7/16	845.5	189.6	D [#] /E ^b	2,489.01	8 5/16	1 7/8	211.0	47.3
E	164.80	32 3/8	7 1/4	821.7	184.2	E	2,637.00	8 1/16	1 13/16	204.6	45.9
F	174.61	31 7/16	7 1/16	797.9	178.9	F	2,794.00	7 7/8	1 3/4	199.9	44.8
F [#] /G ^b	185.00	30 9/16	6 7/8	775.7	173.9	F [#] /G ^b	2,960.00	7 5/8	1 11/16	193.5	43.4
G	196.00	29 11/16	6 5/8	753.5	168.9	G	3,136.00	7 7/16	1 11/16	188.8	42.3
G [#] /A ^b	207.70	28 13/16	6 7/16	731.3	163.9	G [#] /A ^b	3,322.41	7 3/16	1 5/8	182.4	40.9
A	220.00	28	6 1/4	710.6	159.3	A	3,520.00	7	1 9/16	177.7	39.8
A [#] /B ^b	233.10	27 3/16	6 1/8	690.0	154.7	A [#] /B ^b	3,729.20	6 13/16	1 1/2	172.9	38.8
B	246.90	26 7/16	5 15/16	671.0	150.4	B	3,951.00	6 5/8	1 1/2	168.1	37.7
C4	261.60	25 11/16	5 3/4	651.9	146.2	C8	4,186.00	6 7/16	1 7/16	163.4	36.6
C [#] /D ^b	277.20	24 15/16	5 9/16	632.9	141.9	C [#] /D ^b	4,434.81	6 1/4	1 3/8	158.6	35.6
D	293.70	24 1/4	5 7/16	615.5	138.0	D	4,698.40	6 1/16	1 3/8	153.9	34.5
D [#] /E ^b	311.10	23 9/16	5 5/16	598.0	134.1	D [#] /E ^b	4,978.00	5 7/8	1 5/16	149.1	33.4
E	329.61	22 7/8	5 1/8	580.6	130.2	E	5,274.00	5 3/4	1 5/16	145.9	32.7
F	349.30	22 1/4	5	564.7	126.6	F	5,588.00	5 9/16	1 1/4	141.2	31.7
F [#] /G ^b	370.00	21 5/8	4 7/8	548.8	123.1	F [#] /G ^b	5,920.00	5 3/8	1 3/16	136.4	30.6
G	392.00	21	4 11/16	533.0	119.5	G	6,272.00	5 1/4	1 3/16	133.2	29.9
G [#] /A ^b	415.30	20 3/8	4 9/16	517.1	115.9	G [#] /A ^b	6,644.80	5 1/8	1 1/8	130.1	29.2
A	440.01	19 13/16	4 7/16	502.8	112.7	A	7,040.00	4 15/16	1 1/8	125.3	28.1
A [#] /B ^b	466.20	19 1/4	4 5/16	488.6	109.5	A [#] /B ^b	7,458.40	4 13/16	1 1/16	122.1	27.4
B	493.91	18 11/16	4 3/16	474.3	106.3	B	7,902.01	4 11/16	1 1/16	119.0	26.7
						C9	8,367.01	4 9/16	1	115.8	26.0

www.home.fuse.net/engineering/Chimes.htm

Caution, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, but not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A=442, 43 or 44.

Tubular Wind Chime Dimensions

Brass .065 Wall Nominal size = 1 1/4"

A=440 Hz, tube open at both ends

OD inches = 1.250	ID inches = 1.120	Material = Brass
--------------------------	--------------------------	-------------------------

Wall = 0.065 inches * Tubing length calculated for fundamental frequency ** Hang Point is for fundamental frequency node

Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm	Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm
C1	32.70	81 3/4	18 5/16	2,074.8	465.2	C5	523.30	20 7/16	4 9/16	518.7	116.3
C [#] /D ^b	34.60	79 1/2	17 13/16	2,017.7	452.4	C [#] /D ^b	554.40	19 7/8	4 7/16	504.4	113.1
D	36.70	77 3/16	17 5/16	1,959.0	439.2	D	587.30	19 5/16	4 5/16	490.2	109.9
D [#] /E ^b	38.90	75	16 13/16	1,903.5	426.8	D [#] /E ^b	622.30	18 3/4	4 3/16	475.9	106.7
E	41.21	72 13/16	16 5/16	1,848.0	414.3	E	659.30	18 3/16	4 1/16	461.6	103.5
F	43.70	70 3/4	15 7/8	1,795.6	402.6	F	698.50	17 11/16	3 15/16	448.9	100.6
F [#] /G ^b	46.30	68 3/4	15 7/16	1,744.9	391.2	F [#] /G ^b	740.00	17 3/16	3 7/8	436.2	97.8
G	49.00	66 13/16	15	1,695.7	380.2	G	784.00	16 11/16	3 3/4	423.5	95.0
G [#] /A ^b	51.90	64 15/16	14 9/16	1,648.1	369.5	G [#] /A ^b	830.60	16 1/4	3 5/8	412.4	92.5
A	55.01	63 1/16	14 1/8	1,600.5	358.8	A	880.00	15 3/4	3 1/2	399.7	89.6
A [#] /B ^b	58.30	61 1/4	13 3/4	1,554.5	348.5	A [#] /B ^b	932.30	15 5/16	3 7/16	388.6	87.1
B	61.70	59 1/2	13 5/16	1,510.1	338.6	B	987.80	14 7/8	3 5/16	377.5	84.6
C2	65.40	57 13/16	12 15/16	1,467.3	329.0	C6	1,046.50	14 7/16	3 1/4	366.4	82.2
C [#] /D ^b	69.30	56 3/16	12 5/8	1,426.0	319.7	C [#] /D ^b	1,108.70	14 1/16	3 1/8	356.9	80.0
D	73.41	54 9/16	12 1/4	1,384.8	310.5	D	1,174.61	13 5/8	3 1/16	345.8	77.5
D [#] /E ^b	77.80	53	11 7/8	1,345.1	301.6	D [#] /E ^b	1,244.50	13 1/4	3	336.3	75.4
E	82.40	51 1/2	11 9/16	1,307.1	293.0	E	1,318.50	12 7/8	2 7/8	326.8	73.3
F	87.30	50 1/16	11 1/4	1,270.6	284.9	F	1,397.00	12 1/2	2 13/16	317.3	71.1
F [#] /G ^b	92.50	48 5/8	10 7/8	1,234.1	276.7	F [#] /G ^b	1,480.00	12 1/8	2 11/16	307.7	69.0
G	98.01	47 1/4	10 9/16	1,199.2	268.9	G	1,568.00	11 13/16	2 5/8	299.8	67.2
G [#] /A ^b	103.80	45 7/8	10 5/16	1,164.3	261.0	G [#] /A ^b	1,661.20	11 1/2	2 9/16	291.9	65.4
A	110.00	44 9/16	10	1,131.0	253.6	A	1,760.00	11 1/8	2 1/2	282.4	63.3
A [#] /B ^b	116.50	43 5/16	9 11/16	1,099.3	246.5	A [#] /B ^b	1,864.60	10 13/16	2 7/16	274.4	61.5
B	123.50	42 1/16	9 7/16	1,067.5	239.3	B	1,975.50	10 1/2	2 3/8	266.5	59.7
C3	130.81	40 7/8	9 3/16	1,037.4	232.6	C7	2,093.00	10 1/4	2 5/16	260.1	58.3
C [#] /D ^b	138.60	39 11/16	8 7/8	1,007.3	225.8	C [#] /D ^b	2,217.40	9 15/16	2 1/4	252.2	56.5
D	146.80	38 9/16	8 5/8	978.7	219.4	D	2,349.20	9 5/8	2 3/16	244.3	54.8
D [#] /E ^b	155.60	37 1/2	8 7/16	951.8	213.4	D [#] /E ^b	2,489.01	9 3/8	2 1/8	237.9	53.3
E	164.80	36 7/16	8 3/16	924.8	207.3	E	2,637.00	9 1/8	2 1/16	231.6	51.9
F	174.61	35 3/8	7 15/16	897.8	201.3	F	2,794.00	8 7/8	2	225.2	50.5
F [#] /G ^b	185.00	34 3/8	7 11/16	872.4	195.6	F [#] /G ^b	2,960.00	8 5/8	1 15/16	218.9	49.1
G	196.00	33 3/8	7 1/2	847.1	189.9	G	3,136.00	8 3/8	1 7/8	212.6	47.7
G [#] /A ^b	207.70	32 7/16	7 1/4	823.3	184.6	G [#] /A ^b	3,322.41	8 1/8	1 13/16	206.2	46.2
A	220.00	31 1/2	7 1/16	799.5	179.2	A	3,520.00	7 7/8	1 3/4	199.9	44.8
A [#] /B ^b	233.10	30 5/8	6 7/8	777.3	174.3	A [#] /B ^b	3,729.20	7 11/16	1 3/4	195.1	43.7
B	246.90	29 3/4	6 11/16	755.1	169.3	B	3,951.00	7 7/16	1 11/16	188.8	42.3
C4	261.60	28 15/16	6 1/2	734.4	164.7	C8	4,186.00	7 1/4	1 5/8	184.0	41.3
C [#] /D ^b	277.20	28 1/16	6 5/16	712.2	159.7	C [#] /D ^b	4,434.81	7	1 9/16	177.7	39.8
D	293.70	27 5/16	6 1/8	693.2	155.4	D	4,698.40	6 13/16	1 1/2	172.9	38.8
D [#] /E ^b	311.10	26 1/2	5 15/16	672.6	150.8	D [#] /E ^b	4,978.00	6 5/8	1 1/2	168.1	37.7
E	329.61	25 3/4	5 3/4	653.5	146.5	E	5,274.00	6 7/16	1 7/16	163.4	36.6
F	349.30	25	5 5/8	634.5	142.3	F	5,588.00	6 1/4	1 3/8	158.6	35.6
F [#] /G ^b	370.00	24 5/16	5 7/16	617.1	138.3	F [#] /G ^b	5,920.00	6 1/16	1 3/8	153.9	34.5
G	392.00	23 5/8	5 5/16	599.6	134.4	G	6,272.00	5 7/8	1 5/16	149.1	33.4
G [#] /A ^b	415.30	22 15/16	5 1/8	582.2	130.5	G [#] /A ^b	6,644.80	5 3/4	1 5/16	145.9	32.7
A	440.01	22 5/16	5	566.3	127.0	A	7,040.00	5 9/16	1 1/4	141.2	31.7
A [#] /B ^b	466.20	21 11/16	4 7/8	550.4	123.4	A [#] /B ^b	7,458.40	5 7/16	1 1/4	138.0	30.9
B	493.91	21 1/16	4 3/4	534.6	119.8	B	7,902.01	5 1/4	1 3/16	133.2	29.9
						C9	8,367.01	5 1/8	1 1/8	130.1	29.2

www.home.fuse.net/engineering/Chimes.htm

Caution, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, but not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A=442, 43 or 44.

Tubular Wind Chime Dimensions

Brass .065 Wall Nominal size = 1 1/2"

A=440 Hz, tube open at both ends

OD inches = 1.500	ID inches = 1.370	Material = Brass
--------------------------	--------------------------	-------------------------

Wall = 0.065 inches * Tubing length calculated for fundamental frequency ** Hang Point is for fundamental frequency node

Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm	Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm
C1	32.70	89 15/16	20 3/16	2,282.6	511.8	C5	523.30	22 1/2	5 1/16	571.1	128.0
C#/D ^b	34.60	87 7/16	19 5/8	2,219.2	497.5	C#/D ^b	554.40	21 7/8	4 7/8	555.2	124.5
D	36.70	84 15/16	19 1/16	2,155.7	483.3	D	587.30	21 1/4	4 3/4	539.3	120.9
D#/E ^b	38.90	82 1/2	18 1/2	2,093.9	469.4	D#/E ^b	622.30	20 5/8	4 5/8	523.5	117.4
E	41.21	80 1/8	17 15/16	2,033.6	455.9	E	659.30	20 1/16	4 1/2	509.2	114.2
F	43.70	77 13/16	17 7/16	1,974.9	442.8	F	698.50	19 7/16	4 3/8	493.3	110.6
F#/G ^d	46.30	75 5/8	16 15/16	1,919.4	430.3	F#/G ^d	740.00	18 15/16	4 1/4	480.6	107.8
G	49.00	73 1/2	16 1/2	1,865.4	418.2	G	784.00	18 3/8	4 1/8	466.4	104.6
G#/A ^d	51.90	71 7/16	16	1,813.1	406.5	G#/A ^d	830.60	17 7/8	4	453.7	101.7
A	55.01	69 3/8	15 9/16	1,760.7	394.8	A	880.00	17 5/16	3 7/8	439.4	98.5
A#/B ^d	58.30	67 3/8	15 1/8	1,710.0	383.4	A#/B ^d	932.30	16 7/8	3 13/16	428.3	96.0
B	61.70	65 1/2	14 11/16	1,662.4	372.7	B	987.80	16 3/8	3 11/16	415.6	93.2
C2	65.40	63 5/8	14 1/4	1,614.8	362.0	C6	1,046.50	15 7/8	3 9/16	402.9	90.3
C#/D ^b	69.30	61 13/16	13 7/8	1,568.8	351.7	C#/D ^b	1,108.70	15 7/16	3 7/16	391.8	87.8
D	73.41	60 1/16	13 7/16	1,524.4	341.8	D	1,174.61	15	3 3/8	380.7	85.4
D#/E ^b	77.80	58 5/16	13 1/16	1,480.0	331.8	D#/E ^b	1,244.50	14 9/16	3 1/4	369.6	82.9
E	82.40	56 11/16	12 11/16	1,438.7	322.6	E	1,318.50	14 3/16	3 3/16	360.1	80.7
F	87.30	55 1/16	12 3/8	1,397.5	313.3	F	1,397.00	13 3/4	3 1/16	349.0	78.2
F#/G ^d	92.50	53 1/2	12	1,357.8	304.4	F#/G ^d	1,480.00	13 3/8	3	339.5	76.1
G	98.01	51 15/16	11 5/8	1,318.2	295.5	G	1,568.00	13	2 15/16	329.9	74.0
G#/A ^d	103.80	50 1/2	11 5/16	1,281.7	287.4	G#/A ^d	1,661.20	12 5/8	2 13/16	320.4	71.8
A	110.00	49 1/16	11	1,245.2	279.2	A	1,760.00	12 1/4	2 3/4	310.9	69.7
A#/B ^d	116.50	47 11/16	10 11/16	1,210.3	271.4	A#/B ^d	1,864.60	11 15/16	2 11/16	303.0	67.9
B	123.50	46 5/16	10 3/8	1,175.4	263.5	B	1,975.50	11 9/16	2 9/16	293.5	65.8
C3	130.81	45	10 1/16	1,142.1	256.1	C7	2,093.00	11 1/4	2 1/2	285.5	64.0
C#/D ^b	138.60	43 11/16	9 13/16	1,108.8	248.6	C#/D ^b	2,217.40	10 15/16	2 7/16	277.6	62.2
D	146.80	42 7/16	9 1/2	1,077.1	241.5	D	2,349.20	10 5/8	2 3/8	269.7	60.5
D#/E ^b	155.60	41 1/4	9 1/4	1,046.9	234.7	D#/E ^b	2,489.01	10 5/16	2 5/16	261.7	58.7
E	164.80	40 1/16	9	1,016.8	228.0	E	2,637.00	10	2 1/4	253.8	56.9
F	174.61	38 15/16	8 3/4	988.2	221.6	F	2,794.00	9 3/4	2 3/16	247.5	55.5
F#/G ^d	185.00	37 13/16	8 1/2	959.7	215.2	F#/G ^d	2,960.00	9 7/16	2 1/8	239.5	53.7
G	196.00	36 3/4	8 1/4	932.7	209.1	G	3,136.00	9 3/16	2 1/16	233.2	52.3
G#/A ^d	207.70	35 11/16	8	905.7	203.1	G#/A ^d	3,322.41	8 15/16	2	226.8	50.9
A	220.00	34 11/16	7 3/4	880.4	197.4	A	3,520.00	8 11/16	1 15/16	220.5	49.4
A#/B ^d	233.10	33 11/16	7 9/16	855.0	191.7	A#/B ^d	3,729.20	8 7/16	1 7/8	214.1	48.0
B	246.90	32 3/4	7 5/16	831.2	186.4	B	3,951.00	8 3/16	1 13/16	207.8	46.6
C4	261.60	31 13/16	7 1/8	807.4	181.0	C8	4,186.00	7 15/16	1 3/4	201.5	45.2
C#/D ^b	277.20	30 7/8	6 15/16	783.6	175.7	C#/D ^b	4,434.81	7 3/4	1 3/4	196.7	44.1
D	293.70	30	6 3/4	761.4	170.7	D	4,698.40	7 1/2	1 11/16	190.4	42.7
D#/E ^b	311.10	29 3/16	6 9/16	740.8	166.1	D#/E ^b	4,978.00	7 5/16	1 5/8	185.6	41.6
E	329.61	28 5/16	6 3/8	718.6	161.1	E	5,274.00	7 1/16	1 9/16	179.2	40.2
F	349.30	27 1/2	6 3/16	698.0	156.5	F	5,588.00	6 7/8	1 9/16	174.5	39.1
F#/G ^d	370.00	26 3/4	6	678.9	152.2	F#/G ^d	5,920.00	6 11/16	1 1/2	169.7	38.1
G	392.00	26	5 13/16	659.9	147.9	G	6,272.00	6 1/2	1 7/16	165.0	37.0
G#/A ^d	415.30	25 1/4	5 11/16	640.8	143.7	G#/A ^d	6,644.80	6 5/16	1 7/16	160.2	35.9
A	440.01	24 1/2	5 1/2	621.8	139.4	A	7,040.00	6 1/8	1 3/8	155.5	34.9
A#/B ^d	466.20	23 13/16	5 5/16	604.4	135.5	A#/B ^d	7,458.40	5 15/16	1 5/16	150.7	33.8
B	493.91	23 1/8	5 3/16	586.9	131.6	B	7,902.01	5 13/16	1 5/16	147.5	33.1
						C9	8,367.01	5 5/8	1 1/4	142.8	32.0

www.home.fuse.net/engineering/Chimes.htm

Caution, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, but not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A=442, 43 or 44.

Tubular Wind Chime Dimensions

Brass .065 Wall Nominal size = 1 3/4"

A=440 Hz, tube open at both ends

OD inches = 1.750	ID inches = 1.620	Material = Brass
--------------------------	--------------------------	-------------------------

Wall = 0.065 inches * Tubing length calculated for fundamental frequency ** Hang Point is for fundamental frequency node

Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm	Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm
C1	32.70	97 1/2	21 7/8	2,474.6	554.8	C5	523.30	24 3/8	5 7/16	618.6	138.7
C#/D ^b	34.60	94 3/4	21 1/4	2,404.8	539.1	C#/D ^b	554.40	23 11/16	5 5/16	601.2	134.8
D	36.70	92	20 5/8	2,335.0	523.5	D	587.30	23	5 3/16	583.7	130.9
D#/E ^b	38.90	89 3/8	20 1/16	2,268.3	508.6	D#/E ^b	622.30	22 5/16	5	566.3	127.0
E	41.21	86 13/16	19 7/16	2,203.3	494.0	E	659.30	21 11/16	4 7/8	550.4	123.4
F	43.70	84 5/16	18 7/8	2,139.9	479.8	F	698.50	21 1/16	4 3/4	534.6	119.8
F#/G ^d	46.30	81 15/16	18 3/8	2,079.6	466.2	F#/G ^d	740.00	20 1/2	4 5/8	520.3	116.6
G	49.00	79 5/8	17 7/8	2,020.9	453.1	G	784.00	19 15/16	4 1/2	506.0	113.4
G#/A ^d	51.90	77 3/8	17 3/8	1,963.8	440.3	G#/A ^d	830.60	19 5/16	4 5/16	490.2	109.9
A	55.01	75 1/8	16 13/16	1,906.7	427.5	A	880.00	18 13/16	4 3/16	477.5	107.0
A#/B ^d	58.30	73	16 3/8	1,852.7	415.4	A#/B ^d	932.30	18 1/4	4 1/16	463.2	103.8
B	61.70	70 15/16	15 7/8	1,800.4	403.6	B	987.80	17 3/4	4	450.5	101.0
C2	65.40	68 15/16	15 7/16	1,749.6	392.3	C6	1,046.50	17 1/4	3 7/8	437.8	98.2
C#/D ^b	69.30	66 15/16	15	1,698.9	380.9	C#/D ^b	1,108.70	16 3/4	3 3/4	425.1	95.3
D	73.41	65 1/16	14 9/16	1,651.3	370.2	D	1,174.61	16 1/4	3 5/8	412.4	92.5
D#/E ^b	77.80	63 3/16	14 3/16	1,603.7	359.5	D#/E ^b	1,244.50	15 13/16	3 9/16	401.3	90.0
E	82.40	61 3/8	13 3/4	1,557.7	349.2	E	1,318.50	15 3/8	3 7/16	390.2	87.5
F	87.30	59 5/8	13 3/8	1,513.3	339.3	F	1,397.00	14 15/16	3 3/8	379.1	85.0
F#/G ^d	92.50	57 15/16	13	1,470.5	329.7	F#/G ^d	1,480.00	14 1/2	3 1/4	368.0	82.5
G	98.01	56 5/16	12 5/8	1,429.2	320.4	G	1,568.00	14 1/16	3 1/8	356.9	80.0
G#/A ^d	103.80	54 11/16	12 1/4	1,388.0	311.2	G#/A ^d	1,661.20	13 11/16	3 1/16	347.4	77.9
A	110.00	53 1/8	11 15/16	1,348.3	302.3	A	1,760.00	13 5/16	3	337.9	75.8
A#/B ^d	116.50	51 5/8	11 9/16	1,310.2	293.8	A#/B ^d	1,864.60	12 15/16	2 7/8	328.4	73.6
B	123.50	50 1/8	11 1/4	1,272.2	285.2	B	1,975.50	12 9/16	2 13/16	318.8	71.5
C3	130.81	48 3/4	10 15/16	1,237.3	277.4	C7	2,093.00	12 3/16	2 3/4	309.3	69.3
C#/D ^b	138.60	47 3/8	10 5/8	1,202.4	269.6	C#/D ^b	2,217.40	11 13/16	2 5/8	299.8	67.2
D	146.80	46	10 5/16	1,167.5	261.7	D	2,349.20	11 1/2	2 9/16	291.9	65.4
D#/E ^b	155.60	44 11/16	10	1,134.2	254.3	D#/E ^b	2,489.01	11 3/16	2 1/2	283.9	63.7
E	164.80	43 7/16	9 3/4	1,102.4	247.2	E	2,637.00	10 7/8	2 7/16	276.0	61.9
F	174.61	42 3/16	9 7/16	1,070.7	240.1	F	2,794.00	10 9/16	2 3/8	268.1	60.1
F#/G ^d	185.00	41	9 3/16	1,040.6	233.3	F#/G ^d	2,960.00	10 1/4	2 5/16	260.1	58.3
G	196.00	39 13/16	8 15/16	1,010.4	226.5	G	3,136.00	9 15/16	2 1/4	252.2	56.5
G#/A ^d	207.70	38 11/16	8 11/16	981.9	220.1	G#/A ^d	3,322.41	9 11/16	2 3/16	245.9	55.1
A	220.00	37 9/16	8 7/16	953.3	213.7	A	3,520.00	9 3/8	2 1/8	237.9	53.3
A#/B ^d	233.10	36 1/2	8 3/16	926.4	207.7	A#/B ^d	3,729.20	9 1/8	2 1/16	231.6	51.9
B	246.90	35 1/2	7 15/16	901.0	202.0	B	3,951.00	8 7/8	2	225.2	50.5
C4	261.60	34 7/16	7 3/4	874.0	196.0	C8	4,186.00	8 5/8	1 15/16	218.9	49.1
C#/D ^b	277.20	33 1/2	7 1/2	850.2	190.6	C#/D ^b	4,434.81	8 3/8	1 7/8	212.6	47.7
D	293.70	32 1/2	7 5/16	824.9	184.9	D	4,698.40	8 1/8	1 13/16	206.2	46.2
D#/E ^b	311.10	31 5/8	7 1/16	802.6	180.0	D#/E ^b	4,978.00	7 7/8	1 3/4	199.9	44.8
E	329.61	30 11/16	6 7/8	778.8	174.6	E	5,274.00	7 11/16	1 3/4	195.1	43.7
F	349.30	29 13/16	6 11/16	756.6	169.6	F	5,588.00	7 7/16	1 11/16	188.8	42.3
F#/G ^d	370.00	29	6 1/2	736.0	165.0	F#/G ^d	5,920.00	7 1/4	1 5/8	184.0	41.3
G	392.00	28 1/8	6 5/16	713.8	160.0	G	6,272.00	7 1/16	1 9/16	179.2	40.2
G#/A ^d	415.30	27 3/8	6 1/8	694.8	155.8	G#/A ^d	6,644.80	6 13/16	1 1/2	172.9	38.8
A	440.01	26 9/16	5 15/16	674.2	151.1	A	7,040.00	6 5/8	1 1/2	168.1	37.7
A#/B ^d	466.20	25 13/16	5 13/16	655.1	146.9	A#/B ^d	7,458.40	6 7/16	1 7/16	163.4	36.6
B	493.91	25 1/16	5 5/8	636.1	142.6	B	7,902.01	6 1/4	1 3/8	158.6	35.6
						C9	8,367.01	6 1/16	1 3/8	153.9	34.5

www.home.fuse.net/engineering/Chimes.htm

Caution, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, but not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A=442, 43 or 44.

Tubular Wind Chime Dimensions

Brass .065 Wall Nominal size = 2.0"

A=440 Hz, tube open at both ends

OD inches = 2.000	ID inches = 1.870	Material = Brass
--------------------------	--------------------------	-------------------------

Wall = 0.065 inches * Tubing length calculated for fundamental frequency ** Hang Point is for fundamental frequency node

Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm	Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm
C1	32.70	104 7/16	23 7/16	2,650.6	594.3	C5	523.30	26 1/8	5 7/8	663.1	148.7
C#/D ^b	34.60	101 9/16	22 3/4	2,577.7	577.9	C#/D ^b	554.40	25 3/8	5 11/16	644.0	144.4
D	36.70	98 9/16	22 1/8	2,501.5	560.8	D	587.30	24 5/8	5 1/2	625.0	140.1
D#/E ^b	38.90	95 3/4	21 7/16	2,430.1	544.8	D#/E ^b	622.30	23 15/16	5 3/8	607.5	136.2
E	41.21	93 1/16	20 7/8	2,361.9	529.5	E	659.30	23 1/4	5 3/16	590.1	132.3
F	43.70	90 3/8	20 1/4	2,293.7	514.3	F	698.50	22 5/8	5 1/16	574.2	128.7
F#/G ^b	46.30	87 3/4	19 11/16	2,227.1	499.3	F#/G ^b	740.00	21 15/16	4 15/16	556.8	124.8
G	49.00	85 5/16	19 1/8	2,165.2	485.4	G	784.00	21 5/16	4 3/4	540.9	121.3
G#/A ^b	51.90	82 7/8	18 9/16	2,103.4	471.6	G#/A ^b	830.60	20 3/4	4 5/8	526.6	118.1
A	55.01	80 1/2	18 1/16	2,043.1	458.1	A	880.00	20 1/8	4 1/2	510.8	114.5
A#/B ^b	58.30	78 1/4	17 9/16	1,986.0	445.3	A#/B ^b	932.30	19 9/16	4 3/8	496.5	111.3
B	61.70	76 1/16	17 1/16	1,930.5	432.8	B	987.80	19	4 1/4	482.2	108.1
C2	65.40	73 7/8	16 9/16	1,874.9	420.4	C6	1,046.50	18 7/16	4 1/8	467.9	104.9
C#/D ^b	69.30	71 3/4	16 1/16	1,821.0	408.3	C#/D ^b	1,108.70	17 15/16	4	455.3	102.1
D	73.41	69 11/16	15 5/8	1,768.7	396.5	D	1,174.61	17 7/16	3 15/16	442.6	99.2
D#/E ^b	77.80	67 11/16	15 3/16	1,717.9	385.2	D#/E ^b	1,244.50	16 15/16	3 13/16	429.9	96.4
E	82.40	65 13/16	14 3/4	1,670.3	374.5	E	1,318.50	16 7/16	3 11/16	417.2	93.5
F	87.30	63 15/16	14 5/16	1,622.7	363.8	F	1,397.00	16	3 9/16	406.1	91.0
F#/G ^b	92.50	62 1/8	13 15/16	1,576.7	353.5	F#/G ^b	1,480.00	15 1/2	3 1/2	393.4	88.2
G	98.01	60 5/16	13 1/2	1,530.7	343.2	G	1,568.00	15 1/16	3 3/8	382.3	85.7
G#/A ^b	103.80	58 5/8	13 1/8	1,487.9	333.6	G#/A ^b	1,661.20	14 5/8	3 1/4	371.2	83.2
A	110.00	56 15/16	12 3/4	1,445.1	324.0	A	1,760.00	14 1/4	3 3/16	361.7	81.1
A#/B ^b	116.50	55 5/16	12 3/8	1,403.8	314.7	A#/B ^b	1,864.60	13 13/16	3 1/8	350.6	78.6
B	123.50	53 3/4	12 1/16	1,364.2	305.8	B	1,975.50	13 7/16	3	341.0	76.5
C3	130.81	52 1/4	11 11/16	1,326.1	297.3	C7	2,093.00	13 1/16	2 15/16	331.5	74.3
C#/D ^b	138.60	50 3/4	11 3/8	1,288.0	288.8	C#/D ^b	2,217.40	12 11/16	2 7/8	322.0	72.2
D	146.80	49 5/16	11 1/16	1,251.6	280.6	D	2,349.20	12 5/16	2 3/4	312.5	70.1
D#/E ^b	155.60	47 7/8	10 3/4	1,215.1	272.4	D#/E ^b	2,489.01	12	2 11/16	304.6	68.3
E	164.80	46 1/2	10 7/16	1,180.2	264.6	E	2,637.00	11 5/8	2 5/8	295.0	66.1
F	174.61	45 3/16	10 1/8	1,146.9	257.1	F	2,794.00	11 5/16	2 9/16	287.1	64.4
F#/G ^b	185.00	43 15/16	9 7/8	1,115.1	250.0	F#/G ^b	2,960.00	11	2 7/16	279.2	62.6
G	196.00	42 11/16	9 9/16	1,083.4	242.9	G	3,136.00	10 11/16	2 3/8	271.2	60.8
G#/A ^b	207.70	41 7/16	9 5/16	1,051.7	235.8	G#/A ^b	3,322.41	10 3/8	2 5/16	263.3	59.0
A	220.00	40 1/4	9	1,021.5	229.0	A	3,520.00	10 1/16	2 1/4	255.4	57.3
A#/B ^b	233.10	39 1/8	8 3/4	993.0	222.6	A#/B ^b	3,729.20	9 3/4	2 3/16	247.5	55.5
B	246.90	38	8 1/2	964.4	216.2	B	3,951.00	9 1/2	2 1/8	241.1	54.1
C4	261.60	36 15/16	8 5/16	937.5	210.2	C8	4,186.00	9 1/4	2 1/16	234.8	52.6
C#/D ^b	277.20	35 7/8	8 1/16	910.5	204.1	C#/D ^b	4,434.81	8 15/16	2	226.8	50.9
D	293.70	34 7/8	7 13/16	885.1	198.4	D	4,698.40	8 11/16	1 15/16	220.5	49.4
D#/E ^b	311.10	33 7/8	7 5/8	859.7	192.8	D#/E ^b	4,978.00	8 7/16	1 7/8	214.1	48.0
E	329.61	32 7/8	7 3/8	834.4	187.1	E	5,274.00	8 1/4	1 7/8	209.4	46.9
F	349.30	31 15/16	7 3/16	810.6	181.7	F	5,588.00	8	1 13/16	203.0	45.5
F#/G ^b	370.00	31 1/16	6 15/16	788.4	176.8	F#/G ^b	5,920.00	7 3/4	1 3/4	196.7	44.1
G	392.00	30 3/16	6 3/4	766.2	171.8	G	6,272.00	7 9/16	1 11/16	191.9	43.0
G#/A ^b	415.30	29 5/16	6 9/16	744.0	166.8	G#/A ^b	6,644.80	7 5/16	1 5/8	185.6	41.6
A	440.01	28 1/2	6 3/8	723.3	162.2	A	7,040.00	7 1/8	1 5/8	180.8	40.5
A#/B ^b	466.20	27 11/16	6 3/16	702.7	157.5	A#/B ^b	7,458.40	6 15/16	1 9/16	176.1	39.5
B	493.91	26 7/8	6	682.1	152.9	B	7,902.01	6 11/16	1 1/2	169.7	38.1
						C9	8,367.01	6 1/2	1 7/16	165.0	37.0

www.home.fuse.net/engineering/Chimes.htm

Caution, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, but not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A=442, 43 or 44.

Tubular Wind Chime Dimensions

Brass .065 Wall Nominal size = 2 1/4"

A=440 Hz, tube open at both ends

OD inches = 2.250	ID inches = 2.120	Material = Brass
--------------------------	--------------------------	-------------------------

Wall = 0.065 inches * Tubing length calculated for fundamental frequency ** Hang Point is for fundamental frequency node

Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm	Octave Note	A=440 Freq. Hz	Length * inches	Hang Point** inches	Length * mm	Hang Point** mm
C1	32.70	111	24 7/8	2,817.2	631.6	C5	523.30	27 3/4	6 1/4	704.3	157.9
C [#] /D ^b	34.60	107 7/8	24 3/16	2,737.9	613.8	C [#] /D ^b	554.40	26 15/16	6 1/16	683.7	153.3
D	36.70	104 3/4	23 1/2	2,658.6	596.0	D	587.30	26 3/16	5 7/8	664.6	149.0
D [#] /E ^b	38.90	101 3/4	22 13/16	2,582.4	579.0	D [#] /E ^b	622.30	25 7/16	5 11/16	645.6	144.7
E	41.21	98 7/8	22 3/16	2,509.4	562.6	E	659.30	24 11/16	5 9/16	626.6	140.5
F	43.70	96	21 1/2	2,436.5	546.3	F	698.50	24	5 3/8	609.1	136.6
F [#] /G ^b	46.30	93 1/4	20 15/16	2,366.7	530.6	F [#] /G ^b	740.00	23 5/16	5 1/4	591.7	132.7
G	49.00	90 11/16	20 5/16	2,301.6	516.0	G	784.00	22 11/16	5 1/16	575.8	129.1
G [#] /A ^b	51.90	88 1/16	19 3/4	2,235.0	501.1	G [#] /A ^b	830.60	22	4 15/16	558.4	125.2
A	55.01	85 9/16	19 3/16	2,171.6	486.9	A	880.00	21 3/8	4 13/16	542.5	121.6
A [#] /B ^b	58.30	83 1/8	18 5/8	2,109.7	473.0	A [#] /B ^b	932.30	20 13/16	4 11/16	528.2	118.4
B	61.70	80 13/16	18 1/8	2,051.0	459.8	B	987.80	20 3/16	4 1/2	512.4	114.9
C2	65.40	78 1/2	17 5/8	1,992.3	446.7	C6	1,046.50	19 5/8	4 3/8	498.1	111.7
C [#] /D ^b	69.30	76 1/4	17 1/8	1,935.2	433.9	C [#] /D ^b	1,108.70	19 1/16	4 1/4	483.8	108.5
D	73.41	74 1/16	16 5/8	1,879.7	421.4	D	1,174.61	18 1/2	4 1/8	469.5	105.3
D [#] /E ^b	77.80	71 15/16	16 1/8	1,825.8	409.3	D [#] /E ^b	1,244.50	18	4 1/16	456.8	102.4
E	82.40	69 15/16	15 11/16	1,775.0	398.0	E	1,318.50	17 1/2	3 15/16	444.2	99.6
F	87.30	67 15/16	15 1/4	1,724.3	386.6	F	1,397.00	17	3 13/16	431.5	96.7
F [#] /G ^b	92.50	66	14 13/16	1,675.1	375.6	F [#] /G ^b	1,480.00	16 1/2	3 11/16	418.8	93.9
G	98.01	64 1/8	14 3/8	1,627.5	364.9	G	1,568.00	16	3 9/16	406.1	91.0
G [#] /A ^b	103.80	62 5/16	14	1,581.5	354.6	G [#] /A ^b	1,661.20	15 9/16	3 1/2	395.0	88.6
A	110.00	60 1/2	13 9/16	1,535.5	344.3	A	1,760.00	15 1/8	3 3/8	383.9	86.1
A [#] /B ^b	116.50	58 13/16	13 3/16	1,492.7	334.7	A [#] /B ^b	1,864.60	14 11/16	3 5/16	372.8	83.6
B	123.50	57 1/8	12 13/16	1,449.8	325.1	B	1,975.50	14 1/4	3 3/16	361.7	81.1
C3	130.81	55 1/2	12 7/16	1,408.6	315.8	C7	2,093.00	13 7/8	3 1/8	352.1	79.0
C [#] /D ^b	138.60	53 7/8	12 1/16	1,367.3	306.6	C [#] /D ^b	2,217.40	13 1/2	3	342.6	76.8
D	146.80	52 3/8	11 3/4	1,329.3	298.0	D	2,349.20	13 1/16	2 15/16	331.5	74.3
D [#] /E ^b	155.60	50 7/8	11 3/8	1,291.2	289.5	D [#] /E ^b	2,489.01	12 3/4	2 7/8	323.6	72.5
E	164.80	49 7/16	11 1/16	1,254.7	281.3	E	2,637.00	12 3/8	2 3/4	314.1	70.4
F	174.61	48	10 3/4	1,218.2	273.1	F	2,794.00	12	2 11/16	304.6	68.3
F [#] /G ^b	185.00	46 11/16	10 7/16	1,184.9	265.7	F [#] /G ^b	2,960.00	11 11/16	2 5/8	296.6	66.5
G	196.00	45 5/16	10 3/16	1,150.0	257.8	G	3,136.00	11 5/16	2 9/16	287.1	64.4
G [#] /A ^b	207.70	44 1/16	9 7/8	1,118.3	250.7	G [#] /A ^b	3,322.41	11	2 7/16	279.2	62.6
A	220.00	42 13/16	9 5/8	1,086.6	243.6	A	3,520.00	10 11/16	2 3/8	271.2	60.8
A [#] /B ^b	233.10	41 9/16	9 5/16	1,054.9	236.5	A [#] /B ^b	3,729.20	10 3/8	2 5/16	263.3	59.0
B	246.90	40 3/8	9 1/16	1,024.7	229.7	B	3,951.00	10 1/8	2 1/4	257.0	57.6
C4	261.60	39 1/4	8 13/16	996.2	223.3	C8	4,186.00	9 13/16	2 3/16	249.0	55.8
C [#] /D ^b	277.20	38 1/8	8 9/16	967.6	216.9	C [#] /D ^b	4,434.81	9 1/2	2 1/8	241.1	54.1
D	293.70	37	8 5/16	939.1	210.5	D	4,698.40	9 1/4	2 1/16	234.8	52.6
D [#] /E ^b	311.10	36	8 1/16	913.7	204.8	D [#] /E ^b	4,978.00	9	2	228.4	51.2
E	329.61	34 15/16	7 13/16	886.7	198.8	E	5,274.00	8 3/4	1 15/16	222.1	49.8
F	349.30	33 15/16	7 5/8	861.3	193.1	F	5,588.00	8 1/2	1 7/8	215.7	48.4
F [#] /G ^b	370.00	33	7 3/8	837.5	187.8	F [#] /G ^b	5,920.00	8 1/4	1 7/8	209.4	46.9
G	392.00	32 1/16	7 3/16	813.7	182.4	G	6,272.00	8	1 13/16	203.0	45.5
G [#] /A ^b	415.30	31 1/8	7	790.0	177.1	G [#] /A ^b	6,644.80	7 13/16	1 3/4	198.3	44.5
A	440.01	30 1/4	6 13/16	767.7	172.1	A	7,040.00	7 9/16	1 11/16	191.9	43.0
A [#] /B ^b	466.20	29 3/8	6 9/16	745.5	167.1	A [#] /B ^b	7,458.40	7 3/8	1 5/8	187.2	42.0
B	493.91	28 9/16	6 3/8	724.9	162.5	B	7,902.01	7 1/8	1 5/8	180.8	40.5
						C9	8,367.01	6 15/16	1 9/16	176.1	39.5

www.home.fuse.net/engineering/Chimes.htm

Caution, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, but not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A=442, 43 or 44.